

Series 300 Aluminum Single Hung Window

Also Available: Insulated Slider, Insulated Picture Window and Insulated Shapes

- Aluminum frame and sash components are precision cut and assembled to make joints weather-tight
- Warm-edge insulated glass reduces condensation and improves thermal efficiency
- Sashes interlock for added strength and security
- Weather stripping at interlock and sash stile helps block air and water infiltration
- Positive sash lock provides security and helps keep the frame and sash weather-tight
- Half screen* standard
- Full perimeter weather-strip insulation provides energy saving thermal efficiency
- 9/16" insulating glass boosts thermal performance
- Vinyl bulb seal spans bottom of operable sash to minimize air and water infiltration
- Continuous extruded nail-fin on all frame sections for fast, easy installation
- 1" nail-fin setback for brick veneer construction and selected stucco applications
- Sloped-sill allows for easy water run-off
- DP Rating R40 (window size tested 48" x 84")
- Jamb depth: 2.5625"



Color Options**

White



Bronze



Sandstone



Mill




All products may be ordered to meet Energy Star requirements

Custom Options

- Low-E Glass
- Low-E Glass / Argon Gas
- Ultra Low-E / Argon Gas (may be required for Energy Star rating)
- 5/8" or 3/4" flat grids available
- Custom sizes available
- DP-50 (window size tested 48" x 72")

Scan and Experience the WeatherLok Website



*Screens are not meant to restrain a child from falling through an open window.

**Printing process may affect color shown. Please refer to actual window sample when selecting colors.

Manufacturer reserves the right to substitute components as necessary for continued product improvement. WL-300-1/15