

Series 3050 Vinyl Side-Load Single Hung Window

Also Available: Insulated Slider, Insulated Picture Window and Insulated Shapes

- Removable bottom sash
- Industry leading .01 cfm/ft. air infiltration performance
- Multi-cavity vinyl lineals improve thermal performance and enhanced sound absorbency
- Insulating glass provides energy saving thermal efficiency
- Fusion welded frame and sash minimizes air and water infiltration and enhances overall durability
- Sweep lock helps provide a weather-tight seal and added security
- Block and Tackle balance system for ease of operation
- Removable operable sash includes full-length interlock and bottom weather reflector
- Dual screw boss, metal reinforced meeting rail provides added strength
- Custom sized to the nearest 1/8"
- Dual weather-stripping helps block air and water infiltration, keeping harsh elements outside and energy saving comfort inside
- Versatile half-screen* installed from the inside or outside
- Sloped sill reduces air infiltration and accommodates easy water run-off
- Built-in accessory channels accommodate multiple installation options
- Transferable, limited lifetime warranty
- DP Rating R50 (window size tested 36" x 96")
- Jamb depth: 2.625"



Color Options**

White

Almond



All products may be ordered to meet Energy Star requirements

Custom Options

- Low-E Glass
- Low-E Glass / Argon Gas
- Ultra Low-E / Argon Gas (may be required for Energy Star rating)
- 5/8" or 3/4" flat, 5/8" or 1" contoured, 5/8" contoured valance grids available
- Factory mulling of twins, triples and architectural shapes
- Custom sizes available
- Safety latch for sash restriction (field applied)

Scan and Experience the WeatherLok Website



*Screens are not meant to restrain a child from falling through an open window.

**Printing process may affect color shown. Please refer to actual window sample when selecting colors.

Manufacturer reserves the right to substitute components as necessary for continued product improvement. WL-3050-1/15