

Series 3100 Single Hung Window

Also Available: Insulated Slider, Insulated Picture Window and Insulated Shapes

- All-welded frame and sash corners
- Insulated glass panels with optimum thermal air space featuring warm-edge spacer system
- Double sash locks come standard with all windows 27-1/4" or wider
- Aluminum-reinforced lock rail and meeting rails add strength
- Bottom sash tilts in for easy cleaning
- Block & Tackle balance system
- Sloped sill allows easy water run-off
- Factory-installed half screen comes standard*
- Beveled exterior for attractive appearance
- Pre-drilled installation holes
- Head expander and sill angle are included
- 2-5/8" frame width
- Transferable Limited Lifetime Warranty



Factory applied wrap-around foam



All products may be ordered to meet Energy Star requirements



Custom Options

- Low-E Glass
- Low-E Glass / Argon Gas
- Ultra Low-E / Argon Gas (may be required for Energy Star rating; may not be applicable in all zones)
- 5/8" or 3/4" flat, 5/8" or 1" contoured, 5/8" contoured valance grids available
- Custom sizes cut on 1/8" width and height
- Factory mulling of twins and triples
- Charcoal aluminum mesh screen
- Lifetime Glass Breakage Warranty

Scan and Experience the WeatherLok Website

