

## Series 3900 2SL & 3SL Sliding Windows

Also Available: Double Hungs and Picture Windows

- Exclusive InsulKor™ polyurethane fiberglass-enriched sash reinforcement for superior thermal and structural performance
- Fusion-welded sashes and frame add strength and boost insulation
- Low-E glass with insulating argon gas yields outstanding thermal efficiency
- DP 50 rating (window size tested 72" x 48")
- Beveled mainframe offers a stylish exterior appearance
- 4-1/4" frame thickness enhances appearance as well as structural integrity
- External accessory groove accommodates nail fin option
- Full screen\* is standard and removable from the inside
- Dual low profile, positive-action cam locks increase security (2 locks standard at 27-1/4" width or wider)
- Full interlocking lock and meeting rail
- Integrated glide channel for easy sash opening and closing
- Tandem rollers ride easily along friction free glide channel
- Available in 1/4 - 1/2 - 1/4 or 1/3 - 1/3 - 1/3 configurations
- XX 2-lite configuration (both sashes operate)
- 3.25" jamb depth for ideal window sizing
- Transferable limited lifetime warranty
- Lifetime glass breakage warranty



2-Lite Sliding Window



3-Lite Sliding Window

Featuring  
**InsulKor™**  
Technology



### Color Options\*\*



†Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. See full cleaning instructions for details.

### Lock Options\*\*



### Custom Options

- Low-E Glass
- Ultra Low-E / Argon Gas (may be required for Energy Star rating)
- Silent Guard® with noise control STC 34 performance
- Triple-pane, R-5 compliant glass panels
- Super Spacer® nXt™ sealant system for optimal thermal performance (standard with triple-pane option)
- InsulKor™ multi-cavity foam-filled frame injections
- 5/8" or 3/4" flat, 5/8" or 1" contoured, 5/8" contoured valance grids available
- 1-1/8" simulated divided lite (SDL) grid and architectural shapes
- Nail fin accessory for use in remodeling or new construction applications
- Exclusive locking half screen\*
- Obscure or double-strength glass

Scan and Experience the WeatherLok Website



\*Screens are not meant to restrain a child from falling through an open window.  
\*\*Printing process may affect color shown. Please refer to actual window sample when selecting colors.  
Manufacturer reserves the right to substitute components as necessary for continued product improvement. WL-3900SL-1/15