

## Series 5700 Vinyl Horizontal Sliding Window

*Also Available: Insulated Single Hung, Insulated Picture Window and Insulated Shapes*

- 1-1/4" Nail-fin setback for brick veneer construction and select stucco applications
- Sweep lock helps provide a weather-tight seal and added security
- Dual weather-stripping helps block air and water infiltration, keeping harsh elements outside and energy-saving comfort inside
- Versatile half screen\* installs easily from inside
- Double insulated glass provides energy saving efficiency. A host of glass options are available, including Low-E coatings and Argon gas fill for additional efficiency and Energy Star® compliance
- Sloped sill reduces air infiltration and accommodates easy water run-off
- Multi-chambered vinyl lineals improve thermal performance and enhance sound absorbency
- Fusion-welded frame and sash minimizes water and air infiltration and enhances overall durability
- Metal reinforced meeting rail and sash rail provide added durability and enhanced security
- Limited lifetime warranty provides reassuring peace of mind
- Pre-punched integral nail-fin targets proper nail location for quick, easy installation
- Tandem wheel and axle roller assemblies ensure smooth, easy operation on even the largest sizes
- Multi-cavity vinyl lineals improve thermal performance and enhance sound absorbency
- DP Rating R25  
(window size tested 72" x 48")
- Jamb depth: 2.625"



All products may be ordered to meet Energy Star requirements

### Color Options\*\*



### Custom Options

- Low-E Glass
- Low-E Glass / Argon Gas
- Ultra Low-E / Argon Gas  
(may be required for Energy Star rating)
- 5/8" or 3/4" flat, 5/8" or 1" contoured, 5/8" contoured valance grids available
- Custom sizes available

Scan and Experience the WeatherLok Website



\*Screens are not meant to restrain a child from falling through an open window.  
 \*\*Printing process may affect color shown. Please refer to actual window sample when selecting colors.  
 Manufacturer reserves the right to substitute components as necessary for continued product improvement. WL-5700SL-1/15